







ADVANTAGES

- ▶ Easy to Deploy
- ▶ High Definition
- ▶ Multi Platform Support
- ▶ PCT Multi-touch Film
- ▶ Flexible Installation
- ▶ Durable and Professional Embedded Design




> LCD Panel	
Backlight	LED
Brightness	300 cd/m ²
Contrast Ratio	1500:1
Viewing Angle	H:170° / V:170°
Response Time	35 ms (GTG)
Supported Colors	16.7M Colors
Display Resolution	1024 x 768 (4:3)
Display Frame Rate	60Hz
Input Resolution	1024 x 768 @ 60Hz(Analog) 1024 x 768 @ 60Hz(Digital)
> Touch	
Touch points	10
Touch technology	Projected Capacitive (PCT)
> Mechanical	
Dimensions	360.3 x 284.3 x 42.5 mm
Package Dimension	460 x 401.5 x 155 mm
Weight(approximately)	4 kg / 5 kg
Wall Mount Type	VESA, MIS-D,75,C
Connector	1x VGA /1x DVI /1x HDMI
Operation	0 °C ~ 50 °C, 90% RH
Storage	-20 °C ~ 60 °C, 90% RH
> Electrical	
Power Supply	DC in: DC 12V 5A Max
Normal Operation	≤ 10W (typ.)
Power Off	≤ 2 W (typ.)
Internal Speaker	no
> Android(Options)	
CPU	RK3188 Cortex-A9 RK3288 Cortex-A17
Memory	2GB DDR3
ROM	8GB EMMC NAND
Connector	2xUSB /1xLAN /1xHDMI / 1xTF
Options	Signage Software



Monitor



Android



FENIX INVICO, S.A.
 Pacifico, 53-55
 08027 Barcelona
 Phone: +34-93-3539222
 Fax: +34-93-3539721
 E-mail: BCN@fenixinvico.com